

Steatite Slim



ELECTRIC WATER HEATER

Models 30 to 80
(Multi-position installation)



Comfort

- Flat, chrome-plated thermometer
- Easy-to-change heating temperature using simple mechanical controls



Durability

- Steatite technology: ceramic dry heating element protected by a sleeve for limited scaling and easy maintenance
- Magnesium anode to bolster tank protection
- Diamond-quality glass lining
- Pressure relief valve
- Dielectric union
- Specific lip gasket to avoid corrosion around the flange



Installation

- Multi-position: can be installed in vertical and horizontal position, adapting to various interior requirements

Safe operation:

- IP 24 - full compliance with European standards for electrical safety and user protection



Energy savings

- High-efficiency water inlet
- CFC-free high-density insulation to increase energy savings



User-friendly

- Front control knob
- Heating light indicator

- 1** DIAMOND-QUALITY GLASS LINING for extended life and increased reliability
- 2** Optimised stainless steel outlet pipe
- 3** MAGNESIUM ANODE for protection against corrosion
- 4** Inlet diffuser
- 5** Enamel-coated sleeve
- 6** High-density, 0% CFC polyurethane foam




Video:



Steatite
TECHNOLOGY

Steatite dry heating element



Adapted to aggressive, mineralised and desalinated water. Its protective enamel-coated steel sleeve facilitates maintenance, and there is never any need to drain the tank to replace it.

Technical specifications

Model	Output (W)	Voltage (V)	Energy consumption kWh/24 h at 65°C	Heat-up time at 60°C (Δt=50°C)	ErP energy class	Profile
30	1500	230 [220/240]	0.69	1h16		S
50	2100	230 [220/240]	0.90	1h24		M
80	2100	230 [220/240]	1.27	2h15		L

Installation dimensions (mm)

Model	Dimensions (mm)						Net weight (kg)
	A	B	c	D	E	F	
30	597	380	235	139	200	399	14.5
50	850	380	435	184	200	399	19
80	1225	380	700	234	200	399	25

